


# Elements 200 Series

*Recycled rubber flooring that is one of the toughest rubber gym floorings available.*

Built for extreme durability Elements 200 Series can be found in many applications across the United States. Providing optimal shock absorption and extreme support under foot.

- The highest quality rubber gym flooring available
- May qualify for LEED credits as part of a green building project
- Our EPDM color granules are made from 30-100% post consumer




01. Lt. Grey 2125 02. Snow Flakes 2138 03. Blue Sparkle 2127  
04. Blue Pool 2528 05. Crushed Nuts 2153 06. Gold Rush 2529  
07. Red 2109 08. Orange 2527



**portico**  
SYSTEMS

**Flooring Solutions that Simplify.**  
1+ 877 285 8899 • [www.porticosystems.com](http://www.porticosystems.com)



Rubber Flooring

200 Series

# Elements 200 Series

## > HEAVY DUTY COMMERCIAL ROLLED RUBBER FLOORING



### SUGGESTED USES

Weight Rooms, Home Gyms, Fitness Centers, Health Clubs, Recreation Centers, Golf Shops and Golf Courses, Schools and Universities, Play Areas, Day Care Centers, Fire and Police Stations, Physical Therapy Centers, Ice skating facilities, etc.

Construction (ISO 2424):	SBR Rubber Black + 20% Color EPDM/Recycled Rubber
Density (ASTM D3676):	60 pcf - 80 pcf
Hardness (ASTM D2240 (Shore A)):	60 ± 5
Tear Strength (ASTM D624):	70pli - 80 pli min.
Elongation (ASTM D412):	> 75%
Tensile Strength (ASTM D412):	>200 psi
Flexibility (ASTM F137 1/4" Mandrel):	Pass
Resistance to Chemicals (ASTM F825):	No Change
Force Reduction (ASTM F2772)	12.9% - 13.7%
Energy Restitution (ASTM F2772)	85% - 86%
Abrasion Resistance (ASTM D3389)	<1.7g, 1000 cycles
Static Load Limit (ASTM F970)	0.001' @ 250 PSI
Coefficient of Friction (ASTM D2047)	>0.95
Slip Resistance (ASTM F2772)	Pass
VOC Compliant (ASTM D6116 / CA 1350)	Yes
Rolling Load (EN1569)	Pass
Resistance to Impact (EN1517)	14 N/m
Resistance to Identification (EN1516)	0.1mm
Vertical Deformation (ASTM F2772)	1.4mm
Indoor Air Quality (CA Spec 01350):	Pass

### PACKAGING & DIMENSIONS

Size	Colors	Thickness
Roll Goods 4' wide (Standard: 4' x 50' roll)	Lt. Grey 2125, Snow Flakes 2138, Blue Sparkle 2127, Blue Pool 2528, Crushed Nuts 2153, Gold Rush 2529, Red 2109, Orange 2527	9mm (3/8") Thick
Roll Goods 4' wide (Standard: 4' x 50' roll)	Only Orange, Green, Tan (all mixed w/ white)	12mm (1/2") Thick
Square Tile 23" x 23" 500 sq. ft. minimum order (@137 tiles)	All Colors available except Orange, Green and Tan (mixed with white)	9mm (3/8") Thick @ 3.67 sq. ft. / Tile
Interlocking Tile 23" x 23" 500 sq. ft. minimum order (@137 tiles)	Orange, Green and Tan (all mixed with white)	9mm (3/8") Thick @ 3.28 sq. ft. / Tile

LEED-NC

MR Credit 4 | IEQ Credits 4.1, 5

### MAINTENANCE

For maintenance visit [www.porticosystems.com](http://www.porticosystems.com)

### IMPORTANT NOTICE

Sample swatches have been cut from an overall design; decoration and shade may vary.

### LIMITED WARRANTY

Full Commercial Warranty Summary of Warranty

5 years

Products must be professionally installed to validate the warranty.

Portico Systems warrants Elements 200 Series Sheet/Roll Goods against wear for a period of 5 years in a commercial application. This warranty applies only to material that is properly installed and maintained, while being used as intended and recommended. If the defect is covered by this warranty and is reported to Portico Systems within the warranty period, Portico Systems will supply new material of same or similar grade to repair or replace the defective material.

#### Wear

Defined as complete removal of wear layer, pattern and color due to wear from normal traffic and maintenance. If the wear occurs within 5 years from date of purchase, Portico Systems will provide replacement materials or repair, of only the effected area.

#### Manufacturing Defects

Portico Systems warrants Elements 200 Series materials are free from manufacturing defects and will replace defective floor covering and reasonable installation costs for a period of up to one [1] year from date of purchase. Portico Systems will not pay labor costs to repair or replace materials that defects were apparent before or at the time of installation.

#### Other Limitations

- This warranty is non-transferable.
- Manufacturing defect must be reported within 3 months from date of purchase.
- This warranty covers only properly installed & maintained floors.
- Portico Systems excluded and will not pay for any consequential or incidental expenses.
- Portico Systems reserves the right of final judgment and may refuse claims in certain instances.

\*For a copy of the full warranty please ask for a warranty sheet.

### NOTICE ON COLOR VARIATION

This product contains recycled rubber materials, including post-consumer tires. While we make every effort to produce your order from the same rubber log for greater color consistency, variations in shade, tone, and fleck distribution are inherent to recycled content. Such variations are normal, cannot be eliminated, and are not considered defects. Exact color matching between pieces or production batches cannot be guaranteed.

### YOUR AUTHORIZED SALES REPRESENTATIVE:



Experience It For Yourself

Talk with your sales representative or request samples at [samples@porticosystems.com](mailto:samples@porticosystems.com)