


Heron Tile

The ultimate sports, spa and leisure tile for use in wet areas where barefoot traffic is extensive.

Made from soft Ethylene Vinyl Acetate and standing at 5/8" tall, the tiles are designed to deliver extra comfort and excellent drainage. The embossed surface provides a strong grip underfoot, while the anti-microbial and anti-fungal additives ensures excellent hygiene. This winning combination makes Heron Rib tile the ideal slip-resistant tile for swimming pools, gyms and leisure centers.

- Made from flexible PVC
- Seamless coverage for large areas
- Tiles easily click into place for simple installation
- Ease of cleaning with excellent drainage



01. Light Grey



02. Beige



03. Light Blue



04. Ocean Blue



portico
SYSTEMS

Flooring Solutions that Simplify.
1+ 877 285 8899 • www.porticosystems.com



Grid Matting

Heron Tile

Heron Tile



> TILE GRID MATTING SYSTEMS

SUGGESTED USES (Not limited to)

Indoor areas around swimming pools, saunas, jacuzzi, shower areas in locker rooms or other wet areas where barefoot traffic is extensive.

SPECIFICATIONS

Overall Height:	5/8 in. 15mm
Tile Size:	13" x 13" 33 x 33cm
Weight:	0.82 lbs/sq. ft

LIMITED WARRANTY

3 years - Ask for warranty sheet for details

TECHNICAL SPECIFICATIONS (GRID)

Acoustic:	Excellent sound absorption properties
Chemical:	Ask for specific resistances
Composition:	Molded Ethylene Vinyl Acetate (EVA)
Slip Resistance - DIN 51097:	Classification C
UV Light:	Resistant to PVC degradation

CLEANING METHODS BAREFOOT AND WET SIDE MATTING

Regular cleaning as part of planned regime will maintain both the effectiveness and life span of the tiles. All the products incorporate anti-bacterial and anti-fungal additives which are permanent to ensure continued protection. Cleaning is required to remove body fat, light grease and oils, food fat, wax and acrylic polishes.

Prep: Inspect tiles and remove any loose items such as litter and clothing fibers etc.

Hand Cleaning: Regular hand cleaning should be done as required, using an alkaline cleaning fluid* as per the manufacturer's instructions. The tiles can be cleaned in position – simply apply the cleaning solution with a sprayer or mop and allow to penetrate any grease or dirt. You can then use a stiff deck brush to work the cleaning fluid into the surface dirt. Allow to soak before rinsing with clean water.

* JPL Leisure Bright SU201 <http://www.jplennard.com/leisurebright-5-litre.html>

If you're deep cleaning or cleaning the flooring below, the tiles should be lifted up. They shouldn't be folded or pulled, as this will damage them over time.

Machine Cleaning:

How frequently you machine clean will depend on how much traffic the area gets. Spray the surface with the alkaline solution and then, using a cylindrical brush machine, clean the top surface in the direction of the top ribs. If there's an etched pattern on the top ribs where dirt can easily collect, make additional cross passes to ensure a thorough clean.

Steam Cleaning: Any type of steam cleaner may be used. Good results have been obtained with nozzle pressure of approximately 1000 lbs p.s.i. (6894.8 kN/m²) and water temperature of approximately 212°F. Cleaning fluid should be diluted according to the steam cleaning machine manufacturers' recommendations.

HYGIENE

Hygiene: Made from non-porous 100% Virgin EVA, which inhibits the growth of bacteria as it is naturally resistant to bacteria growth.

Incorporates anti-microbial and anti-fungal additives for continuous hygiene. BPR (EU Biocidal Products Regulation 528/2012): Contains Biocidal Products for improved performance.

Anti-bacteria additive: Test JIS Z 2801: 2000
Anti-fungal additive: Test method ASTM G21-09

ENVIRONMENT

Portico Systems does not use any substances currently included in the SVHC (Substances of Very High Concern) list under REACH (Registration, Evaluation, Authorization and Restriction of Chemical substances) in any matting products. All PVC grid products are 100% recyclable.

YOUR AUTHORIZED SALES REPRESENTATIVE:



experience it for yourself

Talk with your sales representative or request samples at samples@porticosystems.com

Grid Matting

Heron Tile