


Premier Nop

Versatile and uncompromising, Premier Nop offers signature performance

Ideally suited for designers looking for style and practicality, this heavy weight material has a berber construction. If you are looking for an easy to fit, high wearing product, Premier Nop Tile is your floor covering choice.

- Made with 100% ASOTA® polypropylene fibers
- UV stable, stain resistant
- Durable and a highly resilient non-woven carpet



- | | | |
|-----------------------|-----------------------|-----------------------|
| 01. Sterling 2344 | 05. Midnight Sky 5154 | 09. Cocoa 1301 |
| 02. Anthracite 1303 | 06. Aspen 6265 | 10. Harvest 1244 |
| 03. Black Shadow 2343 | 07. Sisal 1099 | 11. Bordeaux 7178 |
| 04. Azure 5181 | 08. Brown Sugar 1353 | 12. Cardinal Red 1305 |



Carpet Tiles


Premier Nop



portico
SYSTEMS

Flooring Solutions that Simplify.
1+ 877 285 8899 · www.porticosystems.com

Premier Nop



> 44 OZ. UV STABILIZED BERBER CARPET

SUGGESTED USES

Office Environments, Airports, Conference Rooms, Lobbies, Libraries, Retail/ Department Stores, Resorts, Restaurant Entryways, Spas, etc.

Manufacturing Process: Non-woven
 Surface Aspect: Hobnail (berber) pattern
 Fiber: 100% Solution-dyed UV stabilized ASOTA® polypropylene
 Backing: Premium (eco) Bitumen

Pile Height (± 0.5mm): 0.20"
 Total Height (± 7.5%): 0.47"
 Pile Weight (± 7.5%): 44 oz./sy
 Total Weight (± 7.5%): 172 oz./sy
 Tile Size (± 2%): 19.69" x 19.69"
 Also available in Roll Goods. See Spec Sheet for full details.
 Sheet/Roll Width (± 2%): 6' 7" or 13' 2"

LIMITED WARRANTY

Full Commercial Warranty 5 years
 Summary of Warranty

Products must be professionally installed to validate the warranty. Portico Systems warrants Premier Nop Carpet Tiles against wear for a period of 5 years in a commercial application. This warranty applies only to material that is properly installed and maintained, while being used as intended and recommended. If the defect is covered by this warranty and is reported to Portico Systems within the warranty period, Portico Systems will supply new material of same or similar grade to repair or replace the defective material.

- **Wear**
 Defined as complete removal of wear layer, pattern and color due to wear from normal traffic and maintenance. If the wear occurs within 5 years from date of purchase, Portico Systems will provide replacement materials or repair, of only the effected area.
- **Manufacturing Defects**
 Portico Systems warrants Kensington Premium Nylon materials are free from manufacturing defects and will replace defective floor covering and reasonable installation costs for a period of up to one [1] year from date of purchase. Portico Systems will not pay labor costs to repair or replace materials that defects were apparent before or at the time of installation.
- **Other Limitations**
 - This warranty is non-transferable.
 - Manufacturing defect must be reported within 3 months from date of purchase.
 - This Warranty covers only properly installed & maintained floors.
 - Portico Systems excluded and will not pay for any consequential or incidental expenses.
 - Portico Systems reserves the right of final judgment and may refuse claims in certain instances.

*For a copy of the full warranty please ask for a warranty sheet.

PACKING & DIMENSIONS

Tiles (19.69" x 19.69" ea.): 12 tiles per box (32.5 sq. ft.)

ELECTROSTATIC PROPERTIES

Dimensional Stability (EN 986): Pass
 Electrostatic Propensity (EN 1815): >2kV
 Electrical Resistivity (IBM / ICL): Pass, for R.H. ≥40%
 Sound Insulation (ISO 10140-1:2010): ≥24dB
 Thermal Retention (ISO 11092): Permanently Anti-Static

COLOR FASTNESS

To Light (ISO 105 B02): 5
 To Water (ISO 105 E01): 5
 To Shampoo (ISO 105 C06): 5
 To Rubbing (ISO 105 X12): 4-5 (Dry/Wet)

FLAMMABILITY

Radiant Panel (ASTM E648) Class II
 Smoke Density (ASTM E662) Pass
 Surface Flammability (FF 1-70 / ASTM D285) Pass

LEED-NC

MR Credit 4 | IEQ Credits 4.1, 4.3, 5

INSTALLATION (Tile)

Before laying tiles, it is recommended they are stored at room temperature 60°F-70°F (15°C-20°C). The tiles can be loose laid on flat, dry floors free from impurities such as oil, grease etc. Cracked floors should be filled, and uneven floors covered with hardboard. Dusty floors should be primed. Because of the high insulation value of these tiles it is not recommended they be laid when under-floor heating systems are in use. On very large installations, it is advisable to secure 1 in 5 rows with double-sided tape. Where tiles are to be used under caster chairs, tiles should be fully secured. The tiles may be laid by marking across in the center of the room and working outwards from this, the marker cross may be moved to facilitate the use of tiles in doorways, etc. Tiles must be laid by turning alternate tiles through 90 degrees to obtain a checker pattern. An arrow on the back of each tile indicates the pile direction. Only tiles with the same batch number should be laid together.

*For installation and other information, go to porticosystems.com

MAINTENANCE

Regular vacuuming (Weekly in low-traffic areas, and daily or twice daily in areas with higher traffic) with a motor-driven brush and beater bar can remove up to 80% of surface dirt, and is the easiest way to prolong the life of your carpet.

Regular vacuuming is key to maintaining your carpet, but eventually the carpet color dulls from dirt and grime stuck in the fibers. The dirt is then carried further into the building to form more soil reservoirs. Additionally, the oil content (15%) of the soil causes particles to stick to carpet fiber and resist vacuuming. To restore the carpet to its best condition, frequent light cleaning gives the best result and is often very cost effective.

IMPORTANT NOTICE

Sample swatches have been cut from an overall design; decoration and shade may vary.

YOUR AUTHORIZED SALES REPRESENTATIVE:



experience it for yourself

Talk with your sales representative or request samples at samples@porticosystems.com