

# Safeguard Giant Tiles

*Durable and attractive gym floor cover in the form of easy to handle tiles. Giant-sized mats protect athletic flooring during non-sports events and activities.*

Safeguard Giant Tiles are aesthetically pleasing and used to transform gymnasiums while providing unmatched protection.

- Temporary flooring
- No tools, tape or glue needed for installation
- Quick and easy setup and breakdown
- Industrial strength reusable tiles
- Lightweight
- Slip-resistant and flexible tiles



01. Heather Grey



**portico**  
SYSTEMS

Flooring Solutions that Simplify.  
1+ 877 285 8899 • [www.porticosystems.com](http://www.porticosystems.com)



Carpet Tiles

Safeguard

# Safeguard Giant Tiles



DIVISION  
**9 & 12**

## NON-WOVEN POLYESTER CART TILES

### SUGGESTED USES (NOT LIMITED TO)

Pharmacies, Interior Drive thru areas, Reception areas, or areas where long-term standing is required

Manufacturing Process:	Non-Woven
Fiber:	100% Polyester Non-woven Flat
Primary Backing:	Sure Back Coating
Pile Height (± 0.5mm):	0.228"
Total Weight (± 7.5%):	57.6 oz/sy
Tile Size (± 2%):	39" x 78" (1m x 2m)

### LIMITED WARRANTY

Full Commercial Warranty 5 years

#### Summary of Warranty:

Portico Systems warrants Carpet Tiles against wear for a period of 5 years in a commercial application. This warranty applies only to material that is properly installed and maintained, while being used as intended and recommended. If the defect is covered by this warranty and is reported to Portico Systems within the Warranty period, Portico Systems will supply new material of same or similar grade to repair or replace the defective material. Wear Defined as complete removal of wear layer, pattern and color due to wear from normal traffic and maintenance. If the wear occurs within 1 year from date of purchase, Portico Systems will provide replacement materials or repair, of only the effected area.

#### Manufacturing Defects:

Portico Systems warrants Carpet Tiles materials are free from manufacturing defects and will replace defective floor covering and reasonable installation costs for a period of up to five [5] years from date of purchase. Portico Systems will not pay labor costs to repair or replace materials that defects were apparent before or at the time of installation.

#### Other Limitations:

- This warranty is non-transferable.
- Manufacturing defect must be reported within 3 months from date of purchase.
- This Warranty covers only properly installed & maintained floors.
- Portico Systems excluded and will not pay for any consequential or incidental expenses.

Portico Systems reserves the right of final judgment and may refuse claims in certain instances.

*\*For a copy of the full warranty please ask for a warranty sheet.*

### FLAMMABILITY

Radiant Panel (ASTM E648)	Class II
Smoke Density (ASTM E662)	Pass
Surface Flammability (FF 1-70 / ASTM D2859)	Pass
LEED-NC	MR CREDIT 4   IEQ CREDITS 4.1, 4.3, 5

### INSTALLATION (TILE)

Before laying tiles, it is recommended they are stored at room temperature 60°F-70°F (15°C-20°C). The tiles can be loose laid on flat, dry floors free from impurities such as oil, grease etc. Cracked floors should be filled, and uneven floors covered with hardboard. Dusty floors should be primed. Because of the high insulation value of these tiles it is not recommended they be laid when under-floor heating systems are in use. On very large installations, it is advisable to secure 1 in 5 rows with double-sided tape. Where tiles are to be used under caster chairs, tiles should be fully secured. The tiles may be laid by marking across in the center of the room and working outwards from this, the marker cross may be moved to facilitate these of full tiles in doorways, etc. Tiles must be laid by turning alternate tiles 90 degrees to obtain a checker pattern. An arrow on the back of each tile indicates the pile direction. Only tiles with the same batch number should be laid together.

### MAINTENANCE

Regular vacuuming (Weekly in low-traffic areas, and daily or twice daily in areas with higher traffic) with a motor-driven brush and beater bar can remove up to 80% of surface dirt, and is the easiest way to prolong the life of your carpet. Regular vacuuming is key to maintaining your carpet, but eventually the carpet color dulls from dirt and grime stuck in the fibers. The dirt is then carried further into the building to form more soil reservoirs. Additionally, the oil content (15%) of the soil causes particles to stick to carpet fiber and resist vacuuming. To restore the carpet to its best condition, frequent light cleaning gives the best result and is often very cost effective.

### IMPORTANT NOTICE

Sample swatches have been cut from an overall design; decoration and shade may vary.

### YOUR AUTHORIZED SALES REPRESENTATIVE:



experience it for yourself

Talk with your sales representative or request samples at [samples@porticosystems.com](mailto:samples@porticosystems.com)

Carpet Tiles

Safeguard