

# Synthetic Coco

*Perfect for projecting an environmental or health conscious image.*

The best of two worlds, Synthetic Coco offers the lush, natural look and feel of coconut coir fibers without compromise (or shedding).

- 100 % solution-dyed UV stabilized polypropylene fibers are stain and fade resistant
- Heavy, dense face weight.
- Ideal for long-term usage in even the most heavily-trafficked areas.
- Absorbent surface assists in soaking up water, keeping surrounding floor surfaces dry and safe from slips.
- Best suited for recessed mat wells or wall to wall installations



01.

01. Natural SYN0111



**portico**  
SYSTEMS

**Flooring Solutions that Simplify.**  
1+ 877 285 8899 • [www.porticosystems.com](http://www.porticosystems.com)

AVAILABLE AS  
CUSTOM/LOGO  
MATTING



Carpet/Roll Goods

Synthetic Coco

# Synthetic Coco



## > 44 OZ. NON-WOVEN SMOOTH/VELOUR INDOOR/OUTDOOR MATTING

### SUGGESTED USES

Office Environments, Runners, Conference Rooms, Lobbies, Libraries, Retail/ Department Stores, Entryways, etc.

|                          |  |
|--------------------------|--|
| Manufacturing Process:   | Non-Woven                                      |
| Surface Aspect:          | Non-Directional Smooth/Velour                  |
| Fiber:                   | 100% Solution-dyed UV stabilized polypropylene |
| Backing:                 | Safety Track                                   |
| Pile Height (± 0.5mm):   | 0.422"   |
| Total Height (± 7.5%):   | 0.625"   |
| Pile Weight (± 7.5%):    | 44 oz/sy                                       |
| Total Weight (± 7.5%):   | 120 oz/sy                                      |
| Sheet/Roll Width (± 2%): | 12'  |

### LIMITED WARRANTY

Full Commercial Warranty 5 years

#### Summary of Warranty

Products must be professionally installed to validate the warranty. Portico Systems warrants Synthetic Coco Sheet/Roll Goods against wear for a period of 5 years in a commercial application. This warranty applies only to material that is properly installed and maintained, while being used as intended and recommended. If the defect is covered by this warranty and is reported to Portico Systems within the Warranty period, Portico Systems will supply new material of same or similar grade to repair or replace the defective material.

- **Wear**  
Defined as complete removal of wear layer, pattern and color due to wear from normal traffic and maintenance. If the wear occurs within 5 years from date of purchase, Portico Systems will provide replacement materials or repair, of only the effected area.
- **Manufacturing Defects**  
Portico Systems warrants Synthetic Coco materials are free from manufacturing defects and will replace defective floor covering and reasonable installation costs for a period of up to one [1] year from date of purchase. Portico Systems will not pay labor costs to repair or replace materials that defects were apparent before or at the time of installation.
- **Other Limitations**
  - This warranty is non-transferable.
  - Manufacturing defect must be reported within 3 months from date of purchase.
  - This Warranty covers only properly installed & maintained floors.
  - Portico Systems excluded and will not pay for any consequential or incidental expenses.
  - Portico Systems reserves the right of final judgment and may refuse claims in certain instances.

\*For a copy of the full warranty please ask for a warranty sheet

### PACKAGING & DIMENSIONS

Sheet/Roll Width (± 2%): 12'

### TECHNICAL SPECIFICATIONS

|  |                     |
|--|---------------------|
| Dimensional Stability (ASTM D7570-09): | Pass                |
| Electrostatic Propensity (EN 1815):    | >2kV                |
| Electrical Resistivity (IBM / ICL):    | Pass, for R.H. ≥40% |
| Sound Insulation (ISO 10140-1:2010):   | ≥21dB               |
| Thermal Retention (ISO 11092):         | 0.15 m K/W Pass     |

### COLOR FASTNESS

|                           |                  |
|---------------------------|------------------|
| To Light (ISO 105 B02):   | 6                |
| To Water (ISO 105 E01):   | 5                |
| To Shampoo (ISO 105 C06): | 5                |
| To Rubbing (ISO 105 X12): | 4 (Dry), 5 (Wet) |

### FLAMMABILITY RATING

|  |      |
|--|------|
| Smoke Density (ASTM E662)                    | Pass |
| Surface Flammability (FF 1-70 / ASTM D28591) | Pass |

### LEED-NC

MR CREDIT 4 | IEQ CREDITS 4.1, 4.3, 5

### MAINTENANCE

Regular vacuuming (Weekly in low-traffic areas, and daily or twice daily in areas with higher traffic) with a motor-driven brush and beater bar can remove up to 80% of surface dirt, and is the easiest way to prolong the life of your carpet.

Regular vacuuming is key to maintaining your carpet, but eventually the carpet color dulls from dirt and grime stuck in the fibers. The dirt is then carried further into the building to form more soil reservoirs. Additionally, the oil content (15%) of the soil causes particles to stick to carpet fiber and resist vacuuming. To restore the carpet to its best condition, frequent light cleaning gives the best result and is often very cost effective.

### IMPORTANT NOTICE

Sample swatches have been cut from an overall design; decoration and shade may vary.

### YOUR AUTHORIZED SALES REPRESENTATIVE:



### Experience It For Yourself

Talk with your sales representative or request samples at [samples@porticosystems.com](mailto:samples@porticosystems.com)

Carpet/Roll Goods

Synthetic Coco